



PoE World

World Class
Injectors Switches Splitters
Extenders Testers

Our Locations and Partners : <http://poe-world.com>

PoE-Texas	Austin Texas
Amazon UK / EU	
PoE-World	Shenzhen China

BT-1-WM 1 port PoE injector 802.3af/at/bt auto negotiation 10/100/1000/2.5g



- 1 Port 802.3af/at/bt compliant gigabit Ethernet Injector
 - no power unless a PoE device is attached
 - 1 Shielded RJ-45 LAN
 - 1 Shielded RJ-45 LAN+POE
 - all 4 data pairs active for gigabit data rates
 - shared data and power
- Wall mount Injector: 43 mm x 73mm x 42mm (not including 2x 7mm tabs)
- 90 watts delivered at 100 mtr with 56vdc supply.
- 4 pair PoE operation (type 4)
- 2 pair PoE supported (type 3) and 802.3at/af
- Standard power connector - 2.1mm x 5.5mm
- 5.0 mm connector for awg 16-20 wire
- Wall or DIN rail mounting
- No DC-DC conversion
 - input voltage is the same as the output
- See also our 10g model

Environmental

- Operating temperature range – 0 to 50 deg C
- Storage temperature range – 0 to 50 deg C
- Relative humidity range – 5 to 90% non condensing
- The device is PELV per NFPA standard 79 – protected extra low
- No cooling is required, no fans. Quiet operation



Spring Attachment for DIN Rail mounting

DIN RAIL Mounting

